

Package: rsgeo (via r-universe)

September 3, 2024

Title An Interface to Rust's 'geo' Library

Version 0.1.8

Description An R interface to the GeoRust crates 'geo' and 'geo-types' providing access to geometry primitives and algorithms.

URL <https://github.com/JosiahParry/rsgeo>,
<https://josiahparry.r-universe.dev/rsgeo>,
<https://rsgeo.josiahparry.com/>

License MIT + file LICENSE

Encoding UTF-8

Language en

Roxygen list(markdown = TRUE)

RoxygenNote 7.2.3

Imports rlang, vctrs

Suggests sf, testthat (>= 3.0.0), wk

Config/rextendr/version 0.3.1.9000

SystemRequirements Cargo (Rust's package manager), rustc >= 1.70

Config/testthat/edition 3

Config/Needs/website rmarkdown

Repository <https://josiahparry.r-universe.dev>

RemoteUrl <https://github.com/josiahparry/rsgeo>

RemoteRef HEAD

RemoteSha 5c033a7895ebb2b68fe5a5b398f60fd75030c63c

Contents

rsgeo-package	2
as_rsgeo	3
bearing_geodesic	3
bounding_boxes	4

cast_geoms	5
centroids	6
closest_point	7
combine_geoms	7
coords	9
coord_n	10
densify_euclidean	11
distance_euclidean_pairwise	11
expand_geoms	13
explode_lines	14
flatten_geoms	14
frechet_distance	15
geom_point	16
haversine_destination	17
haversine_intermediate	18
intersects_sparse	18
is_convex	20
length_euclidean	21
line_interpolate_point	22
line_segmentize	22
locate_point_on_line	23
plot.rsgeo	24
signed_area	24
simplify_geoms	26
Index	27

rsgeo-package	<i>rsgeo: An Interface to Rust's 'geo' Library</i>
---------------	--

Description

An R interface to the GeoRust crates 'geo' and 'geo-types' providing access to geometry primitives and algorithms.

Author(s)

Maintainer: Josiah Parry <josiah.parry@gmail.com> ([ORCID](#))

See Also

Useful links:

- <https://github.com/JosiahParry/rsgeo>
- <https://josiahparry.r-universe.dev/rsgeo>
- <https://rsgeo.josiahparry.com/>

as_rsgео	<i>Convert to an rsgео vector</i>
----------	-----------------------------------

Description

Given an vector of geometries, cast it as an rsgео class object.

Usage

```
as_rsgео(x)
```

Arguments

x	a geometry vector
---	-------------------

Value

an object of class rsgео

Examples

```
x <- sf::st_sfc(sf::st_point(c(0,0)))
as_rsgео(x)
```

bearing_geodesic	<i>Calculate Bearing</i>
------------------	--------------------------

Description

Calculates the bearing between two point geometries.

Usage

```
bearing_geodesic(x, y)
```

```
bearing_haversine(x, y)
```

Arguments

x	an object of class rs_POINT
y	an object of class rs_POINT

Value

A vector of doubles of the calculated bearing for between x and y

Examples

```
x <- geom_point(runif(10, 0, 90), rnorm(10, 1, 90))
y <- geom_point(runif(10, 0, 90), rnorm(10, 1, 90))
bearing_geodesic(x, y)
bearing_haversine(x, y)
```

bounding_boxes	<i>Compute Geometric Boundaries</i>
----------------	-------------------------------------

Description

From a vector of geometries identify different types of boundaries.

Usage

```
bounding_boxes(x)

bounding_rect(x)

minimum_rotated_rect(x)

convex_hull(x)

concave_hull(x, concavity)

extreme_coords(x)

bounding_box(x)
```

Arguments

x	an object of class <code>rsgeo</code>
concavity	a value between 0 and 1 specifying the concavity of the convex hull

Details

Note that if you want a convex or concave hull over an entire vector of geometries you must first union or combine them using either `combine_geoms()` or `union_geoms()`

Value

- `bounding_box()` returns a named vector of `xmin`, `ymin`, `xmax`, and `ymax`
- `bounding_boxes()` returns a list of bounding box numeric vectors for each geometry
- `bounding_rect()` returns an `rs_POLYGON` of the bounding rectangle of each geometry
- `convex_hull()` returns an `rs_POLYGON` of the convex hull for each geometry
- `concave_hull()` returns an `rs_POLYGON` of the specified concavity for each geometry

- `extreme_coords()` returns the extreme coordinates of each geometry as a list where each element is a named vector of `xmin`, `ymin`, `xmax`, and `ymax` where each element is a `Point` geometry of the extreme value
- `minimum_rotated_rect()` returns the minimum rotated rectangle covering a geometry as an `rs_POLYGON`

Examples

```
lns <- geom_linestring(
  1:20,
  runif(20, -5, 5),
  rep.int(1:5, 4)
)
bounding_box(lns)
bounding_boxes(lns)
minimum_rotated_rect(lns)
convex_hull(lns)
concave_hull(lns, 0.5)
extreme_coords(lns)
```

cast_geoms

Cast geometries to another type

Description

Cast geometries to another type

Usage

```
cast_geoms(x, to)
```

Arguments

<code>x</code>	an object of class <code>rsgeo</code>
<code>to</code>	a character scalar of the target geometry type. Must be one of "point", "multipoint", "polygon", "multipolygon", "linestring", or "multilinestring".

Details

The below conversions are made available. The left hand column indicates the originating vector class and the right hand column indicates the class that it will can be cast to.

Note that correctness of conversions will not be checked or verified. If you cast an `rs_MULTIPPOINT` to an `rs_POLYGON`, the validity of the polygon cannot be guaranteed.

Conversions from an `rs_POLYGON` into an `rs_LINESTRING` will result in only the exterior ring of the polygon ignoring any interior rings if there are any.

From	To
rs_POINT	rs_MULTIPPOINT
rs_MULTIPPOINT	rs_POLYGON, rs_MULTIPOLYGON, rs_LINESTRING, rs_MULTILINESTRING
rs_POLYGON	rs_MULTIPPOINT, rs_MULTIPOLYGON, rs_LINESTRING, rs_MULTILINESTRING
rs_MULTIPOLYGON	rs_MULTIPPOINT, rs_MULTILINESTRING
rs_LINESTRING	rs_MULTIPPOINT, rs_MULTILINESTRING, rs_POLYGON
rs_MULTILINESTRING	rs_MULTIPPOINT, rs_MULTIPOLYGON

Value

An object of class rsgeo

Examples

```
ply <- geom_polygon(c(0, 1, 1, 0, 0), c(0, 0, 1, 1, 0))
cast_geoms(ply, "linestring")
cast_geoms(ply, "multipoint")
```

centroids	<i>Extract Centroids</i>
-----------	--------------------------

Description

Given a vector of geometries, extract their centroids.

Usage

```
centroids(x)
```

Arguments

x an object of class rsgeo

Value

an object of class rs_POINT

Examples

```
lns <- geom_linestring(1:100, runif(100, -10, 10), rep.int(1:5, 20))
centroids(lns)
```

closest_point	<i>Find Closest Point</i>
---------------	---------------------------

Description

For a given geometry, find the closest point on that geometry to a point. The closest point may be an intersection, a single point, or unable to be determined.

Usage

```
closest_point(x, y)
```

```
closest_point_haversine(x, y)
```

Arguments

x	an object of class <code>rsgeo</code>
y	an object of class <code>rs_POINT</code>

Value

An `rs_POINT` vector

Examples

```
x <- geom_linestring(1:100, runif(100, 0, 90), rep.int(1:10, 10))
y <- geom_point(runif(10, 0, 90), rnorm(10, 1, 90))
closest_point(x, y)
closest_point_haversine(x, y)
```

combine_geoms	<i>Combine geometries</i>
---------------	---------------------------

Description

Given a vector of geometries combine them into a single geometry.

Usage

```
combine_geoms(x)
```

```
union_geoms(x)
```

Arguments

x	an object of class <code>rsgeo</code>
---	---------------------------------------

Details

`combine_geoms()`:

`combine_geoms()` combines a vector of geometries into a vector of length one their MULTI counterpart.

- `rs_POINT` and `rs_MULTIPPOINT` -> `rs_MULTIPPOINT`
- `rs_LINESTRING` and `rs_MULTILINESTRING` -> `rs_MULTILINESTRING`
- `rs_POLYGON` and `rs_MULTIPOLYGON` -> `rs_MULTIPOLYGON`
- `rs_GEOMETRYCOLLECTION` is not supported

`union_geoms()`:

`union_geoms()` creates a union of all geometries removing repeated points or dissolving shared boundaries.

- `rs_POINT` - combines and removes repeated points
- `rs_MULTIPPOINT` - combines removes repeated points
- `rs_LINESTRING` - combines and removes duplicated points
- `rs_MULTILINESTRING` - combines and removes duplicated points
- `rs_POLYGON` - unions geometries into a single geometry
- `rs_MULTIPOLYGON` - unions geometries into a single geometry

Value

An object of class `rsgeo` of length one.

Examples

```
pnts <- geom_point(runif(10), runif(10))
combine_geoms(pnts)

lms <- geom_linestring(1:100, runif(100, -10, 10), rep.int(1:5, 20))
union_geoms(lms)

x <- c(0, 1, 1, 0, 0)
y <- c(0, 0, 1, 1, 0)

p1 <- geom_polygon(x, y)
p2 <- geom_polygon(x - 1, y + 0.5)

z <- c(p1, p2)

res <- union_geoms(z)
res

if (rlang::is_installed(c("sf", "wk"))) {
  plot(z)
  plot(res, lty = 3, border = "blue", add = TRUE, lwd = 4)
}
```

`coords`*Extract Coordinates*

Description

Given an `rsgeo` class object, extract the object's coordinates as a data frame. Empty or missing geometries are ignored.

Usage

```
coords(x)
```

Arguments

`x` an object of class `rsgeo`

Value

A `data.frame` with columns `x`, `y`. Additional columns are returned based on the geometry type. Additional columns are:

- `id`
- `line_id`: refers to the `LineString` ID for `rs_LINESTRING`, or the component `LineString` in a `MultiLineString`, or as the ring ID for a `Polygon`.
- `multilinestring_id`
- `polygon_id`
- `multipolygon_id`

Examples

```
pnt <- geom_point(3, 0.14)
mpnt <- geom_multipoint(1:10, 10:1)
ln <- geom_linestring(1:10, 10:1)
ply <- geom_polygon(c(0, 1, 1, 0, 0), c(0, 0, 1, 1, 0))

coords(pnt)
coords(mpnt)
coords(ln)
coords(union_geoms(rep(ln, 2)))
coords(ply)
coords(union_geoms(rep(ply, 2)))
```

`coord_n`*Coordinate Utilities*

Description

Utility functions for accessing coordinates from a geometry.

Usage

```
coord_n(x, n)
```

```
n_coords(x)
```

```
coord_first(x)
```

```
coord_last(x)
```

Arguments

<code>x</code>	an object of class <code>rsgeo</code>
<code>n</code>	the index position of the coordinate

Details

- `n_coords` returns the total number of coordinates in a geometry
- `coord_first()` returns the first coordinate in a geometry
- `coord_last()` returns the last coordinate in a geometry
- `coord_n()` returns the `nth` coordinate in a geometry

Value

an object of class `rs_POINT`. Whereas `n_coords()` returns an integer vector of the same length as `x`.

Examples

```
lines <- geom_linestring(1:10, 1:10)
n_coords(lines)
coord_first(lines)
coord_last(lines)
coord_n(lines, 5)
```

densify_euclidean	<i>Densify linear geometries</i>
-------------------	----------------------------------

Description

Adds coordinates along a LineString ensuring that no two coordinates are further than a maximum distance apart from each other.

Usage

```
densify_euclidean(x, max_distance)
```

```
densify_haversine(x, max_distance)
```

Arguments

x	an object with linear geometries. Can be an rsgeo object <i>except</i> "rs_POINT" or "rs_MULTIPPOINT".
max_distance	the maximum allowed distance between coordinates.

Details

max_distance expects meters for densify_haversine() whereas densify_euclidean() expects the units of the geometry.

Be sure to use the appropriate densification function based on the type of geometries you have. rsgeo does not check if your coordinates are geographic or planar. It is up to you to choose the correct algorithm.

Examples

```
line <- geom_linestring(1:10, 10:1)
densify_euclidean(line, 0.5)
densify_haversine(line, 100000)
```

distance_euclidean_pairwise	<i>Calculate Distances</i>
-----------------------------	----------------------------

Description

Calculates distances between two vectors of geometries. There are a number of different distance methods that can be utilized.

Usage

```
distance_euclidean_pairwise(x, y)

distance_hausdorff_pairwise(x, y)

distance_vicenty_pairwise(x, y)

distance_geodesic_pairwise(x, y)

distance_haversine_pairwise(x, y)

distance_euclidean_matrix(x, y)

distance_hausdorff_matrix(x, y)

distance_vicenty_matrix(x, y)

distance_geodesic_matrix(x, y)

distance_haversine_matrix(x, y)
```

Arguments

x	and object of class rsgeo
y	and object of class rsgeo

Details

There are `_pairwise()` and `_matrix()` suffixed functions to generate distances pairwise or as a dense matrix respectively. The pairwise functions calculate distances between the *i*th element of each vector. Whereas the matrix functions calculate the distance between each and every geometry.

Euclidean distance should be used for planar geometries. Haversine, Geodesic, and Vicenty are all methods of calculating distance based on spherical geometries. There is no concept of spherical geometries in rsgeo, so choose your distance measure appropriately.

Notes:

- Hausdorff distance is calculated using Euclidean distance.
- Haversine, Geodesic, and Vicenty distances only work with `rs_POINT` geometries.

Value

For `_matrix` functions, returns a dense matrix of distances whereas `_pairwise` functions return a numeric vector.

Examples

```
set.seed(1)
x <- geom_point(runif(5, -1, 1), runif(5, -1, 1))
```

```

y <- rev(x)

distance_euclidean_matrix(x, y)
distance_hausdorff_matrix(x, y)
distance_vicenty_matrix(x, y)
distance_geodesic_matrix(x, y)
distance_haversine_matrix(x, y)

distance_euclidean_pairwise(x, y)
distance_hausdorff_pairwise(x, y)
distance_vicenty_pairwise(x, y)
distance_geodesic_pairwise(x, y)
distance_haversine_pairwise(x, y)

```

expand_geoms

Expand Geometries

Description

Expands geometries into a list of vectors of their components.

Usage

```
expand_geoms(x)
```

Arguments

x an object of class `rsgeo`

Details

- `rs_MULTIPPOINT` expands into a vector of points
- `rs_LINESTRING` expands into a vector points
- `rs_MULTILINESTRING` expands into a vector of linestrings
- `rs_POLYGON` expands into a vector of linestrings
- `rs_MULTIPOLYGON` expands into a vector of polygons

If you wish to have a single vector returned, pass the results into `flatten_geoms()`.

Value

A list of `rsgeo` vectors containing each original geometry's components as a new vector.

Examples

```

mpnts <- geom_multipoint(runif(10), runif(10), rep.int(1:5, 2))
expand_geoms(mpnts)

```

 explode_lines

Explode Lines

Description

Given a LineString or MultiLineString, expand the geometry into each and every component Line.

Usage

```
explode_lines(x)
```

Arguments

x an object of class rs_LINESTRING or rs_MULTILINESTRING

Details

A LineString is composed of one or more Lines. A Line is a connected by a start and end coordinate only.

Value

an object of class rs_LINESTRING

Examples

```
x <- geom_linestring(1:10, 10:1)
length(x)
explode_lines(x)
```

 flatten_geoms

Flatten a list of rsgeo vectors

Description

Flatten a list of rsgeo vectors

Usage

```
flatten_geoms(x)
```

Arguments

x list object where each element is an object of class rsgeo

Value

Returns an object of class `rsgeo`

Examples

```
pnts <- replicate(
  10,
  geom_point(runif(1), runif(1)),
  simplify = FALSE
)

flatten_geoms(pnts)
```

frechet_distance	<i>Calculate Frechet Distance</i>
------------------	-----------------------------------

Description

Given two LineStrings compare thier similarity by calculating the Fréchet distance.

Usage

```
frechet_distance(x, y)
```

Arguments

x	an object of class <code>rs_LINESTRING</code>
y	an object of class <code>rs_LINESTRING</code>

Value

A numeric vector

Examples

```
x <- geom_linestring(1:10, runif(10, -1, 1))
y <- geom_linestring(1:10, runif(10, -3, 3))
frechet_distance(x, y)
```

geom_point*Construct Geometries*

Description

Constructs geometries from numeric vectors.

Usage

```
geom_point(x, y)

geom_multipoint(x, y, id = 1)

geom_linestring(x, y, id = 1)

geom_polygon(x, y, id = 1, ring = 1)

geom_line(x, y)
```

Arguments

x	a vector of x coordinates
y	a vector of y coordinates
id	the feature identifier
ring	the id of the polygon ring

Details

In the case of `geom_line()`, both x and y are vectors of `rs_POINT` geometries. `geom_line()` creates a straight line between two points.

Value

an object of class `rsgeo`

Examples

```
geom_point(3, 0.14)
geom_multipoint(1:10, 10:1)
geom_linestring(1:10, 10:1)
geom_polygon(c(0, 1, 1, 0, 0), c(0, 0, 1, 1, 0))
x <- geom_point(0, 0)
y <- geom_point(5, 0)
geom_line(x, y)
```

haversine_destination *Identify a destination point*

Description

Given a vector of point geometries, bearings, and distances, identify a destination location.

Usage

```
haversine_destination(x, bearing, distance)
```

Arguments

x	an object of class <code>rs_POINT</code>
bearing	a numeric vector specifying the degree of the direction where 0 is north
distance	a numeric vector specifying the distance to travel in the direction specified by bearing in meters

Value

an object of class `rs_POINT`

Examples

```
# create 10 points at the origin
pnts <- geom_point(rep(0, 10), rep(0, 10))

# set seed for reproducibiliy
set.seed(1)

# generate random bearings
bearings <- runif(10, 0, 360)

# generate random distances
distances <- runif(10, 10000, 100000)

# find the destinations
dests <- haversine_destination(pnts, bearings, distances)

# plot points
if (rlang::is_installed(c("sf", "wk"))) {
  plot(pnts, pch = 3)
  plot(dests, add = TRUE, pch = 17)
}
```

haversine_intermediate

Identifies a point between two points

Description

Identifies the location between two points on a great circle along a specified fraction of the distance.

Usage

```
haversine_intermediate(x, y, distance)
```

Arguments

x	an rs_POINT vector
y	an rs_POINT vector
distance	a numeric vector of either length 1 or the same length as x and y

Value

an object of class rs_POINT

Examples

```
x <- geom_point(1:10, rep(5, 10))
y <- geom_point(1:10, rep(0, 10))
res <- haversine_intermediate(x, y, 0.5)
if (rlang::is_installed(c("wk", "sf"))) {
  plot(
    c(x, y, res),
    col = sort(rep.int(c("red", "blue", "purple"), 10)),
    pch = 16
  )
}
```

intersects_sparse

Binary Predicates

Description

Functions to ascertain the binary relationship between two geometry vectors. Binary predicates are provided both pairwise as a sparse matrix.

Usage

```
intersects_sparse(x, y)

intersects_pairwise(x, y)

contains_sparse(x, y)

contains_pairwise(x, y)

within_sparse(x, y)

within_pairwise(x, y)
```

Arguments

x	an object of class rsgeo
y	an object of class rsgeo

Value

- For `_sparse` a list of integer vectors containing the position of the geometry in y
- For `_pairwise` a logical vector

Examples

```
if (rlang::is_installed("sf")) {
  nc <- sf::st_read(
    system.file("shape/nc.shp", package = "sf"),
    quiet = TRUE
  )

  x <- as_rsgeo(nc$geometry[1:5])
  y <- rev(x)

  # intersects
  intersects_sparse(x, y)
  intersects_pairwise(x, y)
  # contains
  contains_sparse(x, y)
  contains_pairwise(x, y)
  # within
  within_sparse(x, y)
  within_pairwise(x, y)
}
```

`is_convex`*Determine the Convexity of a LineString*

Description

For a given `rs_LINSTRING` vector, test its convexity. Convexity can be tested strictly or strongly, as well as based on winding.

Usage

```
is_convex(x)

is_ccw_convex(x)

is_cw_convex(x)

is_strictly_convex(x)

is_strictly_ccw_convex(x)

is_strictly_cw_convex(x)
```

Arguments

<code>x</code>	an object of class <code>rs_LINSTRING</code> See geo docs for further details
----------------	--

Value

a logical vector

Examples

```
lns <- geom_linestring(
  1:20,
  runif(20, -5, 5),
  rep.int(1:5, 4)
)

is_convex(lns)
is_cw_convex(lns)
is_ccw_convex(lns)
is_strictly_convex(lns)
is_strictly_cw_convex(lns)
is_strictly_ccw_convex(lns)
```

length_euclidean	<i>Calculate LineString Length</i>
------------------	------------------------------------

Description

For a given LineString or MultiLineString geometry, calculate its length. Other geometries will return a value of NA.

Usage

```
length_euclidean(x)
```

```
length_geodesic(x)
```

```
length_vincenty(x)
```

```
length_haversine(x)
```

Arguments

x an object of class `rsgeo`

Details**Notes:**

- Vicenty, Geodesic, and Haversine methods will return in units of meters.
- Geodesic length will always converge and is more accurate than the Vicenty methods.
- Haversine uses a mean earth radius of 6371.088 km.

See [geo](#) docs for more details.

Value

A numeric vector

Examples

```
set.seed(0)
y <- runif(25, -5, 5)
x <- 1:25

ln <- geom_linestring(x, y)

length_euclidean(ln)
length_geodesic(ln)
length_vincenty(ln)
length_haversine(ln)
```

line_interpolate_point

Interpolate a Point on a LineString

Description

Finds the point that lies a given fraction along a line.

Usage

```
line_interpolate_point(x, fraction)
```

Arguments

x	an object of class rs_LINestring
fraction	a numeric vector of length 1 or the same length as x. Must be a value between 0 and 1 inclusive.

Value

An object of class rs_POINT

Examples

```
x <- geom_linestring(c(-1, 0, 0), c(0, 0, 1))
line_interpolate_point(x, 0.5)
```

line_segmentize

Segments a LineString into n equal length LineStrings

Description

Given a LineString, segment it into n equal length LineStrings. The n LineStrings are provided as a MultiLineString which can be expanded using expand_geoms() and consequently flattened using flatten_geoms() if desired.

Usage

```
line_segmentize(x, n)
```

```
line_segmentize_haversine(x, n)
```

Arguments

x	and object of class rs_LINestring
n	an integer vector determining the number of equal length LineStrings to create

Details

`line_segmentize()` will segment a `LineString` using a Euclidean length calculation. `line_segmentize_haversine()` will use a Haversine length calculation instead. If you have geometries in a geographic coordinate system such as EPSG:4326 use the Haversine variant. Otherwise, prefer the euclidean variant.

Value

A vector of class `rs_MULTILINESTRING`

Examples

```
x <- geom_linestring(1:10, runif(10, -1, 1))  
segs <- line_segmentize(x, 3)  
flatten_geoms(  
  expand_geoms(segs)  
)
```

<code>locate_point_on_line</code>	<i>Locate a Point on a LineString</i>
-----------------------------------	---------------------------------------

Description

Calculates the fraction of a `LineString`'s length to a point that is closes to a corresponding point in `y`.

Usage

```
locate_point_on_line(x, y)
```

Arguments

<code>x</code>	an object of class <code>rs_LINESTRING</code>
<code>y</code>	an object of class <code>rs_POINT</code>

Value

A numeric vector containing the fraction of of the `LineString` that would need to be traveled to reach the closest point.

Examples

```
x <- geom_linestring(c(-1, 0, 0), c(0, 0, 1))  
y <- geom_point(-0.5, 0)  
locate_point_on_line(x, y)
```

plot.rsgeo

Plot Geometries

Description

Plot Geometries

Usage

```
## S3 method for class 'rsgeo'
plot(x, ...)
```

Arguments

x	an object of class rsgeo
...	arguments passed to wk::wk_plot()

Details

Plotting geometries utilizes wk::wk_plot(). The rust geometries are handled by first converting to an sfc object in the wk::wk_handle() method thus requiring both packages for plotting.

Value

Nothing.

Examples

```
if (rlang::is_installed(c("sf", "wk"))) {
  plot(geom_linestring(1:10, runif(10)))
}
```

signed_area

Calculate the area of a polygon

Description

Functions to calculate different types of area for polygons.

Usage

```
signed_area(x)

unsigned_area(x)

signed_area_cd(x)

unsigned_area_cd(x)

signed_area_geodesic(x)

unsigned_area_geodesic(x)
```

Arguments

x an object of class `rsgeo`

Details

- functions assume counter clock-wise winding in accordance with the simple feature access standard
- functions ending in `_cd` use the Chamberlain-Duquette algorithm for spherical area
- Chamberlain-Duquette and Geodesic areas are returned in meters squared and assume non-planar geometries

See geo docs for more:

- [GeodesicArea](#)
- [Area](#)
- [ChamberlainDuquetteArea](#)

Value

a numeric vector of the area contained by the geometry

Examples

```
x <- c(0, 1, 1, 0, 0)
y <- c(0, 0, 1, 1, 0)
p <- geom_polygon(x, y)

signed_area(p)
unsigned_area(p)
signed_area_cd(p)
unsigned_area_cd(p)
signed_area_geodesic(p)
unsigned_area_geodesic(p)
```

simplify_geoms	<i>Simplify Geometry</i>
----------------	--------------------------

Description

Simplifies LineStrings, Polygons, and their Multi- counterparts.

Usage

```
simplify_geoms(x, epsilon)
simplify_vw_geoms(x, epsilon)
simplify_vw_preserve_geoms(x, epsilon)
```

Arguments

x	an object of class of rsgео
epsilon	a tolerance parameter. Cannot be equal to or less than 0.

Details

Simplify functions use the Ramer–Douglas–Peucker algorithm. Functions with vw use the Visvalingam-Whyatt algorithm.

For more see [geo docs](#).

Value

an object of class rsgео

Examples

```
x <- geom_linestring(1:100, runif(100, 5, 10))

simplify_geoms(x, 3)
simplify_vw_geoms(x, 2)
simplify_vw_preserve_geoms(x, 100)
```

Index

as_rsgeo, [3](#)

bearing_geodesic, [3](#)

bearing_haversine (bearing_geodesic), [3](#)

bounding_box (bounding_boxes), [4](#)

bounding_boxes, [4](#)

bounding_rect (bounding_boxes), [4](#)

cast_geoms, [5](#)

centroids, [6](#)

closest_point, [7](#)

closest_point_haversine
(closest_point), [7](#)

combine_geoms, [7](#)

concave_hull (bounding_boxes), [4](#)

contains_pairwise (intersects_sparse),
[18](#)

contains_sparse (intersects_sparse), [18](#)

convex_hull (bounding_boxes), [4](#)

coord_first (coord_n), [10](#)

coord_last (coord_n), [10](#)

coord_n, [10](#)

coords, [9](#)

densify_euclidean, [11](#)

densify_haversine (densify_euclidean),
[11](#)

distance_euclidean_matrix
(distance_euclidean_pairwise),
[11](#)

distance_euclidean_pairwise, [11](#)

distance_geodesic_matrix
(distance_euclidean_pairwise),
[11](#)

distance_geodesic_pairwise
(distance_euclidean_pairwise),
[11](#)

distance_hausdorff_matrix
(distance_euclidean_pairwise),
[11](#)

distance_hausdorff_pairwise
(distance_euclidean_pairwise),
[11](#)

distance_haversine_matrix
(distance_euclidean_pairwise),
[11](#)

distance_haversine_pairwise
(distance_euclidean_pairwise),
[11](#)

distance_vicenty_matrix
(distance_euclidean_pairwise),
[11](#)

distance_vicenty_pairwise
(distance_euclidean_pairwise),
[11](#)

expand_geoms, [13](#)

explode_lines, [14](#)

extreme_coords (bounding_boxes), [4](#)

flatten_geoms, [14](#)

frechet_distance, [15](#)

geom_line (geom_point), [16](#)

geom_linestring (geom_point), [16](#)

geom_multipoint (geom_point), [16](#)

geom_point, [16](#)

geom_polygon (geom_point), [16](#)

haversine_destination, [17](#)

haversine_intermediate, [18](#)

intersects_pairwise
(intersects_sparse), [18](#)

intersects_sparse, [18](#)

is_ccw_convex (is_convex), [20](#)

is_convex, [20](#)

is_cw_convex (is_convex), [20](#)

is_strictly_ccw_convex (is_convex), [20](#)

is_strictly_convex (is_convex), [20](#)

is_strictly_cw_convex (is_convex), [20](#)

`length_euclidean`, [21](#)
`length_geodesic` (`length_euclidean`), [21](#)
`length_haversine` (`length_euclidean`), [21](#)
`length_vincenty` (`length_euclidean`), [21](#)
`line_interpolate_point`, [22](#)
`line_segmentize`, [22](#)
`line_segmentize_haversine`
 (`line_segmentize`), [22](#)
`locate_point_on_line`, [23](#)

`minimum_rotated_rect` (`bounding_boxes`), [4](#)

`n_coords` (`coord_n`), [10](#)

`plot.rsgeo`, [24](#)

`rsgeo` (`rsgeo-package`), [2](#)
`rsgeo-package`, [2](#)

`signed_area`, [24](#)
`signed_area_cd` (`signed_area`), [24](#)
`signed_area_geodesic` (`signed_area`), [24](#)
`simplify_geoms`, [26](#)
`simplify_vw_geoms` (`simplify_geoms`), [26](#)
`simplify_vw_preserve_geoms`
 (`simplify_geoms`), [26](#)

`union_geoms` (`combine_geoms`), [7](#)
`unsigned_area` (`signed_area`), [24](#)
`unsigned_area_cd` (`signed_area`), [24](#)
`unsigned_area_geodesic` (`signed_area`), [24](#)

`within_pairwise` (`intersects_sparse`), [18](#)
`within_sparse` (`intersects_sparse`), [18](#)